

**PROCEEDINGS**

**ENGINEERING WORKSHOP  
ON  
PEAK REDUCTION  
FOR DRAINAGE AND FLOOD CONTROL PROJECTS**

**MAY 9, 1987**

**Sponsored by**

**AMERICAN SOCIETY OF CIVIL ENGINEERS  
LOS ANGELES SECTION, ORANGE COUNTY BRANCH**



**DEPARTMENT OF CIVIL ENGINEERING  
CALIFORNIA STATE UNIVERSITY, LONG BEACH**



**AMERICAN SOCIETY OF CIVIL ENGINEERS  
STUDENT CHAPTER  
CALIFORNIA STATE UNIVERSITY, LONG BEACH**



PROCEEDINGS

ENGINEERING WORKSHOP ON PEAK REDUCTION  
FOR DRAINAGE AND FLOOD CONTROL PROJECTS  
MAY 9, 1987

Sponsored by

AMERICAN SOCIETY OF CIVIL ENGINEERS  
LOS ANGELES SECTION, ORANGE COUNTY BRANCH

DEPARTMENT OF CIVIL ENGINEERING  
CALIFORNIA STATE UNIVERSITY, LONG BEACH

AMERICAN SOCIETY OF CIVIL ENGINEERS  
STUDENT CHAPTER  
CALIFORNIA STATE UNIVERSITY, LONG BEACH

The opinions expressed in and the responsibility for the contents of the articles herein published are those of the authors. They are not to be construed as the opinions of the California State University, Long Beach or the University's Department of Civil Engineering.

WORKSHOP CO-CHAIRMEN

M. Gamal Mostafa  
Professor of Civil Engineering  
California State University, Long Beach  
Long Beach, California

and

Gary Dysart  
Senior Vice President  
Willdan Associates  
Anaheim, California

WORKSHOP HOST COMMITTEE

Ali Eshett  
Professor of Civil Engineering  
California State University, Long Beach

Mauricio Diaz  
President, ASCE Student Chapter  
California State University, Long Beach

Roberto DeLeon  
Vice President, ASCE Student Chapter  
California State University, Long Beach

## TABLE OF CONTENTS

KEYNOTE ADDRESS . . . . . 1

Lt. Col. Norman Jackson

### FIRST SESSION: HYDRAULICS

"Hydraulics of Spatially-Variied Flow"  
M. Gamal Mostafa . . . . . 3

"Case Study: Mathematical and Physical Modeling  
of Peak Reduction in Supercritical Flow"  
M. Gamal Mostafa . . . . . 13

"Diversion Structure for Peak Flow Reduction"  
Hasan Nouri . . . . . 26

"Case Study on Peak Flow and Velocity Reduction"  
Violet Chu, Jerry Sterling and H. L. Chu . . . . . 30

### SECOND SESSION: PLANNING

"An Overview of Master Planning and Peak Reduction"  
John M. Tettermer . . . . . 45

"The Negative Aspects of Detention Basins"  
Phillip Jones, Jerry Sterling and James Williams . . . . . 50

"Analysis of Detention and Non-Detention Flood  
Control Master Plan Facilities in the San  
Diego Creek Drainage Area"  
Alan A. Swanson and Mark A. Smiley . . . . . 61

"Reducing Rate of Runoff for Small Urban Areas"  
Max D. Withrow . . . . . 80

### THIRD SESSION: HYDROLOGY

"Peak Flow Reduction Systems and Hydraulic Models -  
A Review of Progress"  
A. J. Nestlinger and T. V. Hromodka, III . . . . . 88

"Including Uncertainty in the Design of Flood  
Control Peak Reduction Systems"  
T. V. Hromodka, III . . . . . 103

"Use of Kinematic Wave Theory with Rational Method"  
Iraj Nasserri . . . . . 125

PEAK FLOW REDUCTION SYSTEMS AND HYDROLOGIC MODELS -  
A REVIEW OF PROGRESS

A. J. Nestlinger, M.ASCE<sup>1</sup> and T. V. Hromadka II, M.ASCE<sup>2</sup>

ABSTRACT: The usual procedure in designing flood control peak reduction systems is to rely on computational results produced from a particular hydrologic modeling approach. Advances in hydrologic modeling techniques typically involves the incorporation of higher complexity into the hydrology model by use of improved hydraulic submodels or a more refined approximation of the several subprocesses integrated in the hydrologic cycle. With over 150 models reported in the open literature, it is appropriate to review the progress achieved by the complexification of hydrologic models. That is, it is time to evaluate whether the general level of success afforded by the many types of complex models provide a marked improvement over that achieved by the more commonly used and simpler models such as the unit hydrograph method (UH). Because of the lack of success reported in the use of models more complex than the simple single area UH method, it may be questionable in using any method other than the UH approach when designing peak flow reduction systems.

## INTRODUCTION

A review of the literature indicates that a substantial evolution in modeling complexity has occurred over the last two decades. The majority of changes have occurred in the incorporation of soil moisture accounting techniques and intricate link-node model discretization using approximations for hydraulics. However in spite of the advances made in the modeling complexity, the accuracy of models (in general) has not been significantly improved in the correlation of rain gage data to stream gage runoff data. Only a handful of papers and reports are available in the open literature which compare modeling performance, and each of these reports note that simpler models do as good as or better than complex models. Additionally, many of the papers indicate that the uncertainty in the effective rainfall distribution over the catchment may be a key factor in the lack of major gains in the development, calibration, and application, of hydrologic models. As a result of this lack in demonstrated success in the use of any particular advanced modeling technique or approach, there is continued reliance by the engineering community to use the more simpler modeling approaches such as the rational method for peak flow rate estimates, or the classic unit hydrograph method when a runoff hydrograph is needed such as for dams or retarding basins.

In this paper, the literature is reviewed to identify trends which support using simpler models such as the unit hydrograph method (more specifically, the design storm/unit hydrograph approach used in the Orange and San Bernardino County Hydrology Manuals). From these trends, suggestions as to how the more complex modeling techniques may "prove" themselves to the designers of retarding structures and, therefore, find more use in the engineering community.

- 
- 1 Risk Manager, Orange County Environmental Management Agency, Santa Ana, California
  - 2 Director of Water Resources Engineering, Williamson and Schmid, Irvine, California, and Research Associate, Princeton University, New Jersey

## MODEL SELECTION

... the selection of the hydrologic model, the need for both runoff peak flow rates and runoff volumes (for the testing of detention basins) require the selection of a model that produces a runoff hydrograph. The U.S. Army Corps of Engineers (COE) Hydrologic Engineering Center (HEC) Training Document (TD) No. 11, (1980) categorizes all hydrologic models into eight groupings of which three develop a runoff hydrograph; namely single event (design storm), multiple discrete events, and continuous records (continuous simulation). These models can be further classified according to the submodels employed. For example, a unit hydrograph or a kinematic wave model may be used to represent the catchment hydraulics.

In a survey of hydrologic model usage by Federal and State governmental agencies and private engineering firms (U.S. Department of Transportation, Federal Highway Administration, Hydraulic Engineering Circular No. 19, October 1984), it was found that "practically no use is made of watershed models for discrete event and continuous hydrograph simulation." In comparison, however, design storm methods were used from 24 to 34 times more frequently than the complex models by Federal agencies and the private sector, respectively. The frequent use of design storm methods appear to be due to several reasons: (1) design storm methods are considerably simpler to use than discrete event and continuous simulation models; (2) it has not been established in general that the more complex models provide an improvement in computational accuracy over design storm models; and (3) the level of complexity typically embodied in the continuous simulation class of models does not appear to be appropriate for the catchment rainfall-runoff data which is typically available. Consequently, the design storm approach is most often selected for flood control and drainage policies. Considerations in the choice of modeling approach are contained in the latter sections.

The next decision is whether to use the standard unit hydrograph method or the more recently advanced kinematic wave method to model catchment hydraulics. Again, it has not been clearly established that the kinematic wave approach (e.g., the overland flow plane concept) provides an improvement in modeling accuracy over the unit hydrograph approach that has been calibrated to local rainfall-runoff data. Pilgrim (1986) notes that, "while this [KW routing of overland flow planes] allows a fairly rigorous mathematical treatment, the physical realism of sheet type overland flow on either natural or urban watersheds is open to serious question. It must also be questioned whether models embodying these plane surfaces provide better practical design procedures than the simpler procedures in current use...Surprisingly, little field evidence is available on the realism of the assumed sheet flow."

For the choice of design storm to be used, the work of Beard and Chang (1979) and HEC ("Hypothetical Floods", 1975) provide a logical motivation for developing a design storm using rainfalls of identical return frequency, adjusted for watershed area effects.

Finally, specific components of the modeling approach must be selected and specified. Inherent in the choice of submodels is the ability to calibrate the model at two levels: (1) calibration of model parameters to represent local or regional catchment rainfall-runoff characteristics, and (2) calibration of the model parameters (or design storm) to represent local rainfall intensity-duration-frequency characteristics. Beard and Chang (1979) note that in a hydrologic model, the number of calibration parameters should be as small as possible in order to correlate model parameters with basin characteristics. They also write that a regional study should be prepared to establish the loss rate and unit hydrograph characteristics, "and to compute from balanced storms or selected frequencies (storms having the same rainfall frequency for all durations) the resulting floods."

## LITERATURE REVIEW

### CHOICE OF WATERSHED MODEL

In developing a flood control and drainage policy for detention basins, the first, and possibly the most important question to answer is: what type of model should be used to form the basis for design calculations? To answer this question, the literature was reviewed extensively. Based on the research findings summarized in the following paragraphs, the design storm/unit hydrograph (UH) method appears to have continued support among practitioners. The question naturally arises as to why the simple UH method continues to be the dominant hydrologic tool when considerably more complex models are available for public use (e.g., the continuous simulation class of models which has a mathematical approximation for each component of the hydrologic cycle, and typically utilizes physically based hydraulic flow routing approximations. The Stanford Watershed Model is an excellent example of this class of approach.) An explanation frequently cited in the literature appears to be that the uncertainty in the effective rainfall over the catchment overshadows the improved accuracy that may be possibly achieved by more complex models.

Pilgrim (1986) notes, "There is a common, even if not explicit, assumption held by researchers that more accurate flood estimates will be obtained as improved and generally more complex methods of flood estimation are developed. This is in spite of the well-known problems of decreased efficiency of estimation of parameters as model complexity increases."

A criterion for complex and simple models is given by Beard and Chang (1979) as the "difficulty or reliability of model calibration...Perhaps the simplest type of model that produces a flood hydrograph is the unit hydrograph model"...and..."can be derived to some extent from physical drainage features but fairly easily and fairly reliably calibrated through successive approximations by relating the time distribution of average basin rainfall excess to the time distribution of runoff." In comparison, the "most complicated type of model is one that represents each significant element of the hydrologic process by a mathematical algorithm. This is represented by the Stanford Watershed Model and requires extensive data and effort to calibrate."

The literature contains several reports of problems in using complex models, especially in parameter optimization. Additionally, it has not been clearly established whether complex models, such as in the continuous simulation or discrete event classes of models, provide an increase in accuracy over a standard design storm unit hydrograph model.

There are only a few papers and reports in the literature that provide a comparison in hydrologic model performance. From these references, it appears that a simple unit hydrograph model provides as good as or better results than quasi-physically based (or QPB, see the work of Loague and Freeze (1985)) or complex models.

In their paper, Beard and Chang (1979) write that in the case of the unit hydrograph model, "the function of runoff versus rainfall excess is considered to be linear, whereas it usually is not in nature. Also, the variations in shapes of unit hydrographs are not derivable directly from physical factors. However, models of this general nature are usually as representative of physical conditions as can reasonably be validated by available data, and there is little advantage in extending the degree of model sophistication beyond validation capability." It is suggested that "if 50 yr-100 yr of streamflow were available for a specified condition of watershed development, a frequency curve of flows for that condition can be constructed from a properly selected set of flows."

Schilling and Fuches (1986) write "that the spatial resolution of rain data input is of paramount importance to the accuracy of the simulated hydrograph" due to "the high spatial variability of storms" and "the amplification of rainfall sampling errors by the nonlinear transformation" of rainfall into runoff. Their recommendations are that a model should employ a simplified surface flow model if there are many subbasins; a simple runoff coefficient loss rate; and a diffusion (zero inertia) or storage channel routing technique. Hornberger, et al. (1985) write that "Even the most physically based models...cannot reflect the true complexity and heterogeneity of the processes occurring in the field. Catchment hydrology is still very much an empirical science."

In attempting to define the modeling processes by the available field data forms Hornberger, et al find that "Hydrological quantities measured in the field tend to be either integral variables (e.g., stream discharge, which reflects an integrated catchment response) or point estimates of variables that are likely to exhibit marked spatial and/or temporal variation (e.g., soil hydraulic conductivity)." Hence, the precise definition of the physics in a modeling sense becomes a problem that is "poorly posed in the mathematical sense." Typically, the submodel parameters cannot be adequately estimated due to the large associated estimation error. "Such difficulties often indicate that the structural complexity of the model is greater than is warranted on the basis of the calibration data set."

Schilling and Fuchs (1986) note that errors in simulation occur for several reasons including:

1. The input data, consisting of rainfall and antecedent conditions, vary throughout the watershed and cannot be precisely measured.
2. The physical laws of fluid motion are simplified.
3. Model parameter estimates may be in error."

By reducing the rainfall data set resolution from a grid of 81 gages to a single catchment-centered gage in an 1,800 acre catchment, variations in runoff volumes and peak flows "is well above 100 percent over the entire range of storms implying that the spatial resolution of rainfall has a dominant influence on the reliability of computed runoff." It is also noted that "errors in the rainfall input are amplified by the rainfall-runoff transformation" so that "a rainfall depth error of 30 percent results in a volume error of 60 percent and peak flow error of 80 percent."

Schilling and Fuches (1986) also write that "it is inappropriate to use a sophisticated runoff model to achieve a desired level of modeling accuracy if the spatial resolution of rain input is low" (in their study, the raingage densities considered for the 1,800-acre catchment are 81-, 9-, and a single centered gage).

In a similar vein, Beard and Chang (1979) write that in their study of 14 urban catchments, complex models such as continuous simulation typically have 20 to 40 parameters and functions that must be derived from recorded rainfall-runoff data. "Inasmuch as rainfall data are for scattered point locations and storm rainfall is highly variable in time and space, available data are generally inadequate in this region for reliably calibrating the various interrelated functions of these complex models." Additionally, "changes in the model that would result from urbanization could not be reliably determined." They write that the application "of these complex models to evaluating changes in flood frequencies usually requires simulation of about 50 years of streamflow at each location under each alternative watershed condition."



Garen and Burges (1981) noted the difficulties in rainfall measurement for use in the Stanford Watershed Model, because the K1 parameter (rainfall adjustment factor) and UZSN parameter (upper level storage) had the dominant impact on the model sensitivity. This is especially noteworthy because Dawdy and O'Donnell (1965) concluded that insensitive model coefficients could not be calibrated accurately. Hence, they could not be reliably used to measure physical effects of watershed changes.

Using another complex model, Mein and Brown (1978) write that on "the basis of several tests with the Boughton model it is concluded that for this model at least, relationships derived between any given parameter value and measureable watershed characteristics would be imprecise; i.e., they would have wide confidence limits. One could not be confident therefore in changing a particular parameter value of this model and then claiming that this alteration represented the effect of some proposed land use change. On the other hand, the model performed quite well in predicting flows with these insensitive parameters, showing that individual parameter precision is not a prerequisite to satisfying output performance."

According to Gburek (1971), "...a model system is merely a researcher's idea of how a physical system interacts and behaves, and in the case of watershed research, watershed models are usually extremely simplified mathematical descriptions of a complex physical situation...until each internal submodel of the overall model can be independently verified, the model remains strictly a hypothesis with respect to its internal locations and transformations..." (also quoted in McPherson and Schneider, (1974)).

The introduction of a paper by Sorooshian and Gupta (1983) provides a brief review of some of the problems reported by other researchers in attempting to find a "true optimum" parameter set for complex models, including the unsuccessful two man-year effort by Johnson and Pilgrim (1976) to optimize parameters for a version of the Boughton model cited above.

In the extensive study by Loague and Freeze (1985), three event based rainfall-runoff models (a regression model, a unit hydrograph model, and a kinematic wave quasi-physically based model) were used on three data sets of 269 events from three small upland catchments. In that paper, the term "quasi-physically based" or QPB is used for the kinematic wave model. The three catchments were 25 acres, 2.8 square miles, and 35 acres in size, and were extensively monitored with rain gage, stream gage, neutron probe, and soil site testing.

For example, the 25 acre site contained 35 neutron probe access sites, 26 soil parameter sites (all equally spaced), an on-site rain gage, and a stream gage. The QPB model utilized 22 overland flow planes and four channel segments. In comparative tests between the three modeling approaches to measured rainfall-runoff data it was concluded that all models performed poorly and the QPB performance was only slightly improved by calibration of its most sensitive parameter, hydraulic conductivity. They write that the "conclusion one is forced to draw...is that the QPB model does not represent reality very well; in other words, there is considerable model error present. We suspect this is the case with most, if not all conceptual models currently in use." Additionally, "the fact that simpler, less data intensive models provided as good or better predictions than a QPB is food for thought." Pilgrim (1986) also quotes Loague and Freeze extensively.

Based on the above selected sample of literature, the main difficulty in the use, calibration, and development, of complex models appears to be the lack of precise rainfall data and the high model sensitivity to (and magnification of) rainfall

measurement errors. Nash and Sutcliffe (1970) write that "As there is little point in applying exact laws to approximate boundary conditions, this, and the limited ranges of the variables encountered, suggest the use of simplified empirical relations."

It is noteworthy to consider the HEC Research Note No. 6 (1979) where the Hydrocomp HSP continuous simulation model was applied to the West Branch DuPage River in Illinois. Personnel from Hydrocomp, HEC, and COE participated in this study which started with a nearly complete hydrologic/meteorologic data base. "It took one person six months to assemble and analyze additional data, and to learn how to use the model. Another six months were spent in calibration and long-record simulation." This time allocation applies to only a 28.5 square mile basin. The quality of the final model is indicated by the average absolute monthly volume error of 32.1 and 28.1 percent for calibration and verification periods, respectively. Peak flow rate average absolute errors were 26 and 36 percent for calibration and verification periods, respectively. It was concluded that "Discharge frequency under changing urban conditions is a problem that could be handled by simpler, quicker, less costly approaches requiring much less data; e.g., design storms or several historical events used as input to a single-event model, or a continuous model with a less complex soil-moisture accounting algorithm."

The complex model parameter optimization problem has not been resolved. For example, Gupta and Sarooshian (1983) write that "even when calibrated under ideal conditions (simulation studies), it is often impossible to obtain unique estimates for the parameters" Troutman (1982) also discusses the often cited difficulties with the error in precipitation measurements "due to the spatial variability of precipitation." This source of error can result in "serious errors in runoff prediction and large biases in parameter estimates by calibration of the model."

Because it still has not been well established in the open literature whether there is a significant advantage in using a watershed model more complex or physically based than a design storm unit hydrograph approach, the design storm unit hydrograph method will probably have continued widespread use among practitioners for flood control design and planning studies.

#### NONLINEARITY: USE OF A NONLINEAR KINEMATIC WAVE METHOD OR A LINEAR UNIT HYDROGRAPH METHOD

The dominant method used in runoff hydrograph development for representing catchment runoff response is the unit hydrograph (UH). The next most frequently used method is the kinematic wave overland flowplane concept (KW). HEC TD#15 (1982) provides a description and comparison of these two alternatives. The relative use of KW by 1983 is indicated in Cermak and Feldman (1983) who write that "actual applications by Corps field offices have been few to nonexistent. Even at HEC the KW approach has not been utilized in any special assistance projects." The relatively small usage of KW were then explained as being due to the lack of demand for hydrologic studies and due to unfamiliarity with the technique.

Watt and Kidd (1975) write that in the comparison of so-called 'physically-based' or 'black-box' modeling types (e.g., UH or n-linear reservoirs) the differences are not clear. For example, "except for certain 'ideal' laboratory catchments, the flow does not conform to the sheet-flow model but instead occurs in many small rivulets...The choice is then between a 'black-box' model and a 'physically-based' model which is based on a physical situation quite different than the actual field situation, i.e., a 'black-box' model."

However, use of KW implies a non-linear response whereas the UH implies a linear response. Nash and Sutcliffe (1970) write that "the UH assumption of a linear time invariant relationship cannot be tested because neither the input (effective rainfall) or output (storm runoff) are unequivocally defined." Although watershed response is often considered to be mathematically nonlinear, the nonlinearity of the total watershed response has not been shown to be exactly described as a KW. Indeed, a diffusion hydrodynamic model, DHM (Hromadka and Yen, 1986), provides another nonlinear watershed response that includes an additional term in the governing St. Venant flow equations and that may differ significantly in response from a KW model (e.g. overland flow planes with KW channel routing). There are an infinity of nonlinear mathematical representations possible as a combination of surface runoff and channel routing analogs, therefore, merely claiming that the response of a watershed model can be classified as 'nonlinear' is not proof that the model represents the true response of the catchment.

Given that the KW analog is only used to obtain an approximation to catchment response, the KW approach does not appear to provide significantly better computational results (for floods of interest in flood control design and planning) than the commonly used UH method. Dickinsen, et al (1967) noted that "in the range of discharges normally considered as flood hydrographs, the time [of concentration] remained virtually constant. In other words, in the range of flood interest, the nonlinear effect approached linearity." An explanation was advanced that "at low discharges, the mean velocity may vary considerably with discharge. However, for higher discharges contained within banks, the mean velocity in the channel remains approximately constant.

In actual travel time measurements of flows in a 96-acre catchment using a radioactive tracing technique (Pilgrim (1976) noted that although the flood runoff process "is grossly nonlinear at low flows, linearity is approximated at high flows." Pilgrim also writes that "simple nonlinear models fitted by data from events covering the whole range of flow may give gross errors when used to estimated large events. It is noted that overbank flow was one of the factors for linearity in this study.

Beven (1979) proposed to place limits on the nonlinearity associated to KW by the specification of a constant flow velocity for catchment runoff for large floods. He proposes "a nonlinear channel system for low flows and a linear system at high flows into a single model." Hence for flood flows of interest in flood control planning and design, Beven's model would reduce to a linear representation of the catchment hydraulics.

A physical test of the KW concept was provided by Hjelmfelt and Burwell (1984), who studies a set of 40 similar erosion plots and the net response to storm events. Due to the large variability in measured runoff quantities from the plots, however, it was concluded that a criterion for a valid rainfall-runoff model "is that it predicts the mean runoff for each event." However, it is noted that this test may be more of a test of effective rainfall variability over the catchment than a test of KW response.

In HEC Technical Paper No. 59 (1978), six models, plus two variants of one of these models and a variant of another, were calibrated and tested on a 5.5 square mile urban catchment in Castro Valley near Oakland, California. Both single event and continuous simulation models based on both UH and KW techniques were used in the test. The study concluded that for this watershed "the more complex models did not produce better results than the simple models..." An examination of the test results between the KW and HEC-1 models did not show a clear difference between the methods.

Pilgrim (1986) notes that "...there is now much field evidence that power type non-linearity is not true for many watersheds and that although small floods are grossly nonlinear, linearity is often approximated at the high flows of interest in design."

It is of interest that Singh (1977) concluded that "if one is not very confident in estimates of watershed infiltration then in some circumstances linear models may have an advantage over nonlinear models in runoff peak predictions because they do not amplify the input errors." That is, the uncertainty in effective rainfall quantities may be magnified by a nonlinear model; consequently, there is an advantage in using a linear model when there are errors in loss rate and precipitation estimates.

Because it has not been well established whether the nonlinear KW method for modeling surface runoff provides an improvement in accuracy over the linear UH based hydrologic models, the UH model will probably continue to be the most often used runoff model among practitioners.

## DESIGN STORMS

HEC (Beard, 1975) provides an in-depth study of the use of design runoff hydrographs for flood control studies. "Hypothetical floods consists of hydrographs of artificial flood flows...that can be used as a basis for flood-control planning, design and operation decisions or evaluations. These floods represent classes of floods of a specified or implied range of severity." Such "floods are ordinarily derived from rainfall or snowmelt or both, with ground conditions that are appropriate to the objectives of the study, but they can be derived from runoff data alone, usually on the basis of runoff volume and peak-flow frequency studies and representative time sequences of runoff."

In complex watershed systems that include catchment subareas, and channel and basin routing components, Beard (1975) writes that "it is usually necessary to simulate the effects of each reservoir on downstream flows for all relevant magnitudes of peaks and volumes of inflows. Here it is particularly important that each hypothetical flood has a peak flow and volumes for all pertinent durations that are commensurate in severity, so that each computed regulated flow will have a probability or frequency that is comparable to that of the corresponding unregulated flow...In the planning of a flood control project involving storage or in the development of reservoir operation rules, it is not ordinarily known what the critical duration will be, because this depends on the amounts of reservoir space and release in relation to flood magnitude. When alternate types of projects are considered, critical durations will be different, and a design flood should reflect a degree of protection that is comparable for the various types of projects."

Beard (1975) notes that the balanced storm concept is an important argument for not using a historic storm pattern or sequence of storm patterns (e.g., continuous simulation or discrete event modeling) as "No one historical flood would ordinarily be representative of the same severity of peak flow and runoff volumes for all durations of interest." Indeed, should a continuous simulation study be proposed such that the "project is designed to regulate all floods of record, it is likely that one flood will dictate the type of project and its general features, because the largest flood for peak flows is also usually the largest-volume flood." Hence a continuous simulation model of say 40 years of data can be thought of as a 40 year duration design storm with its own probability of re-occurrence, which typically reduces for modeling purposes to simply a single or double day storm pattern.

Beard and Chang (1979) write that for design storm construction, "it is generally considered that a satisfactory procedure is to construct an approximately symmetrical

pattern of rainfall with uniform areal distribution having intensities for all durations corresponding to the same recurrence interval and for that location and size of area" (i.e., depth-area effects).

Pilgrim (1986) notes that "while they [simulation techniques] are attractive theoretically, none of these approaches is widely used at present, and it is unlikely that any will make serious inroads on the use of a single design flood in the foreseeable future...most researchers of rainfall-runoff phenomena are oriented toward deterministic problems, whereas the major practical applications are for probabilistic design...A design flood is generally a probabilistic estimate whereas a flood from an actual storm is of a deterministic nature...parameter values for a flood estimation procedure need to be derived in a manner that corresponds with the way in which the procedure will be used...Design values should be derived probabilistically and mean or median values may be satisfactory."

The nested design storm concept is developed in detail in HEC TD#15 (1982), including the use of depth-area adjustments. Again, because the current alternatives to the design storm approach (i.e., continuous simulation or discrete event modeling) have not been well established in the literature to provide more accurate estimates of flood frequency values, the design storm approach probably will have continued widespread usage among practitioners.

#### MODEL SELECTION

Of the over 150 models available, a design storm/unit hydrograph model (i.e., "model") is currently the most widely used modeling technique among practitioners. Some of the reasons are as follows: (1) the design storm approach--the multiple discrete event and continuous simulation categories of models have not been clearly established to provide better predictions of flood flow frequency estimates for evaluating the impact of urbanization and for design flood control systems than a calibrated design storm model; (2) the unit hydrograph method--it has not been shown that the kinematic wave modeling technique provides a significantly better representation of watershed hydrologic response than a model based on unit hydrographs (locally calibrated) that represent free-draining catchments; (3) model usage--the "model" has been used extensively nationwide and has proved generally acceptable and reliable; (4) parameter calibration--the "model" usually is based on a minimal number of parameters, generally giving higher accuracy in calibration of model parameters to rainfall-runoff data, and the design storm to local flood flow frequency tendencies; (5) calibration effort--the "model" does not require large data or time requirements for calibration; (6) application effort--the "model" does not require a large computational effort for application; (7) acceptability--the "model" uses algorithms (e.g., convolution, etc.) that have gained acceptance in engineering practice; (8) model flexibility for planning--data handling and computational submodels can be coupled to the "model" (e.g., channel and basin routing) resulting in a highly flexible modeling capability; (9) model certainty evaluation--the certainty of modeling results can be readily evaluated as a distribution of possible outcomes over the probabilistic distribution of parameter values.

#### FURTHER RESEARCH NEEDS

Even though there are many hydrologic and "physically based" models reported in the literature which contain algorithms to model each of the specific hydrologic cycle processes, the basic "design storm/unit hydrograph" method continues to be the most widely used approach among practitioners. It appears that for another class of model to become the engineering standard tool, the model must clearly demonstrate the benefits in its use for the corresponding increase in computational effort. Such demonstrations include exhaustive comparisons of modeling performance in accuracy

and reliability; not only in the reproduction of known storm events, but in the estimate of flood frequency peak flow rate estimates. Finally, storm runoff hydrograph analyses should include verification runs, where the storms tested are not elements of the calibration data set.

## CONCLUSIONS

Although modern hydrologic models have reached a high level of elegance in the mathematical approximation of the rainfall-runoff process, the simpler models such as the classic unit hydrograph approach continue to be the most widespread used study tool among practitioners. In this paper, a review of the literature indicates that the more complex models have not sufficiently proven themselves to be significantly better computational tools. Indeed, many key reports indicate that the simpler UH modeling approach provides computational results which are as good as or better than those achieved by the more complex models.

Based on the selected literature, the uncertainty in the effective rainfall distribution over the catchment appears to be a major limitation to the successful development, calibration, and usage, of any hydrologic model. And this uncertainty in effective rainfall appears to be more of a problem to complex model performance than for simpler model's performance.

## REFERENCES

1. Akan, A., Yen, B., Diffusion - Wave Flood Routing in Channel Networks, Journal of Hydraulics Division, Proceedings of the American Society of Civil Engineers, Vol. 107, No. HY6, June, 1981.
2. Alonso, C., Stochastic Models of Suspended-Sediment Dispersion, Journal of Hydraulic Engineering, Proceedings of the American Society of Civil Engineers, Vol. 107, No. HY6, June, 1981.
3. Beard, L., Chang, S., Journal of the Hydraulics Division, Urbanization Impact of Streamflow, June, 1974.
4. Beard, L., Impact of Hydrologic Uncertainties on Flood Insurance, Journal of the Hydraulic Division, American Society of Civil Engineers, Vol. 104, No. HY11, November, 1978.
5. Bell, F., Estimating Design Floods From Extreme Rainfall, Hydrology Papers, Colorado State University, Fort Collins, Colorado, No. 29, June, 1968.
6. Beven, K., On the Generalized Kinematic Routing Method, Water Resources Research, Vol. 15, No. 5, October, 1979.
7. Bree, T., The General Linear Model with Prior Information, Journal of Hydrology, 39 (1978) 113-127, Elsevier Scientific Publishing Company, Amsterdam-Printed in The Netherlands.
8. Cermak, R., Feldman, A., Urban Hydrologic Modeling Using HEC-1/Kinematic Wave, Presented at the 19th Annual AWRA Conference, October 9-13, 1983, San Antonio, Texas.
9. Chien, J., Sarikelle, S., Synthetic Design Hyetograph and Rational Runoff Runoff Coefficient, Journal of the Irrigation and Drainage Division, Vol. 102, No. 1R3, September, 1976.

10. Chow, V., Kulandaiswamy, V., The IUH of General Hydrologic Systems Model, Journal of the Hydraulics Division. Proceedings of the American Society of Civil Engineers, Vol. 108, No. HY7, July, 1982.
11. Crippen, J., Envelope Curves for Extreme Flood Events, Journal of the Hydraulic Division, Vol. 108, No. HY10, October, 1982.
12. Dawdy, D., Bergman, J., Effect of Rainfall Variability on Streamflow Simulation, Water Resources Research, Vol. 5, No. 5, October, 1969.
13. Dawdy, D., O'Donnell, T., Mathematical Models of Catchment Behavior, Journal of the Hydraulics Division, Vol. 91, No. HY4, July, 1965.
14. Debo, T., Urban Flood Damage Estimating Curves, Journal of the Hydraulics Division, Vol. 108, No. HY10, October, 1982.
15. Dickinson, W., et al, An Experimental Rainfall-Runoff Facility, No. 25, Hydrology Papers, Colorado State University, Fort Collins, Colorado, September, 1967.
16. Fleming, G., Franz, D., Flood Frequency Estimating Techniques for Small Watersheds, Journal of the Hydraulics Division, Vol. 97, No. HY 9, September, 1971.
17. Fogel, M., Duckstein, L., Point Rainfall Frequencies in Convective Storms, Water Resources Research, Vol. 5, No. 6, December, 1969.
18. Garen, D., Burges, S., Approximate Error Bounds for Simulated Hydrographs, Journal of the Hydraulics Division, Proceedings of the American Society of Civil Engineers, ASCE, Vol. 107, No. HY11, November, 1981.
19. Gundlach, A., Adjustment of Peak Discharge Rates for Urbanization, Journal of the Irrigation and Drainage Division, American Society of Civil Engineers, Vol. 104, No. 1R3, September, 1978.
20. Gupta, V., Sorooshian, S., Uniqueness and Observability of Conceptual Rainfall-Runoff Model Parameters: The Percolation Process Examined, Water Resources Research, Vol. 19, No. 1, pp. 269-276, February, 1983.
21. Hjalmarson, H., Flash Flood in Tanque Verde Creek, Tucson, Arizona, Journal of Hydraulic Engineering, Vol. 110, No. 12, December, 1984.
22. Hjelmfelt, A., Burwell, R., Spatial Variability of Runoff, Journal of Irrigation and Drainage Engineering, Vol. 110, No. 1, March, 1984.
23. Hjelmfelt, A., Convolution and the Kinematic Wave Equations, Journal of Hydrology, 75 (1984/1985) 301-309, Elsevier Science Publishers B.V., Amsterdam-Printed in The Netherlands.
24. Hollis, G., The Effect of Urbanization on Floods of Different Recurrence Interval, Water Resources Research, Vol. 11, No. 3, June, 1975.
25. Hornberger, et al, Shenandoah Watershed Study: Calibration of A Topography-Based, Variable Contributing Area Hydrological Model to a Small Forested Catchment, Water Resources Research, Vol. 21, No. 12, December, 1985.
26. Hromadka II, T. V. and Yen, C. C., A Diffusion Hydrodynamic Model, Advances in Water Resources, Vol. 9, No. 3, pp. 118-170, 1986.

27. Huang, Y., Channel Routing by Finite Different Method, Journal of the Hydraulics Division, Vol. 104, No. HY10, October 17, 1977.
28. Hydrological Engineering Center, Corps of Engineers, U.S. Army, Davis, California, Vol. 5, March, 1975.
29. Hydrology, U.S. Department of Transportation, Federal Highway Administration, Hydraulic Engineering Circular No. 19, October, 1984.
30. Johnston, P., Pilgrim, D., Parameter Optimization for Watershed Models, Water Resources Research, Vol. 12, No. 3, June, 1976.
31. Katopodes, N., Schamber, D., Applicability of Dam-Break Flood Wave Models, Journal of Hydraulic Engineering, Vol. 109, No. 5, May, 1983.
32. Keefer, T., Comparison of Linear Systems and Finite Differences Flow-Routing Techniques, Water Resources Research, Vol. 12, No. 5, October, 1976.
33. Kelway, P., The Rainfall Recorder Problem, Journal of Hydrology, 26 (1975) 55-77, Elsevier Scientific Publishing Company, Amsterdam-Printed in The Netherlands.
34. Kite, G., Confidence Limits for Design Events, Water Resources Research, Vol. 11, No. 1, February, 1975.
35. Klemes, V., Bulu, A., Limited Confidence in Confidence Limits Derived by Operational Stochastic Hydrologic Models, Journal of Hydrology, 42 (1979) 9-22, Elsevier Scientific Publishing Company, Amsterdam-Printed in The Netherlands.
36. Lee, L., Essex, T., Urban Headwater Flooding Damage Potential, Journal of Hydraulic Engineering, Vol. 109, No. 4, April, 1983.
37. Loague, K., Freeze, R., A Comparison of Rainfall-Runoff Modeling Techniques on Small Upland Catchments, Water Resources Research, Vol. 21, No. 2, February, 1984.
38. Hawsley, J., Tagg, A., Identification of Unit Hydrographs From Multi-Event Analysis, Journal of Hydrology, 49 (1981) 315-327, Elsevier Scientific Publishing Company, Amsterdam-Printed in The Netherlands.
39. Mein, R. G., Brown, B. M., Sensitivity of Optimized Parameters in Watershed Models, Water Resources Research, Vol. 14, No. 2, April, 1978.
40. Mays, L., Coles, L., Optimization of Unit Hydrograph Determination, Journal of the Hydraulics Division, American Society of Civil Engineers, Vol. 106, No. HY1, January, 1980.
41. Mays, L., Taur, C., Unit Hydrograph via Nonlinear Programming, Water Resources, Vol. 18, No. 4, pp. 744-752, August, 1982.
42. McCuen, R., Bondelid, T., Estimating Unit Hydrograph Peak Rate Factors, Journal of Irrigation and Drainage Engineering, Vol. 109, No. 2, June, 1983.
43. McCuen, R., et al, Estimating Urban Time of Concentration, Journal of Hydraulic Engineering, Vol. 110, No. 7, July, 1984.



44. McCuen, R., et al, SCS Urban Peak Flow Methods, Journal of Hydraulic Engineering, Vol. 110, No. 3, March, 1984.
45. McCuen, R. H., Yen, C. C., and Hromadka II, T. V., Adjusting Stream Gage Data for Urbanization Effects, Microsoftware for Engineers, 1987.
46. McPherson, M., Schmeider, R., Problems in Modeling Urban Watersheds, Water Resources Research, Vol. 10, No. 3, June, 1974.
47. Nash, J., Sutcliffe, J., River Flow Forecasting Through Conceptual Models Part 1 - A Discussion of Principles, Journal of Hydrology, 10, pp.282-290, 1970.
48. Neff, E., How Much Rain Does A Rain Gage Gage?, Journal of Hydrology, 35 (1977) 213-220, Elsevier Scientific Publishing Company, Amsterdam-Printed in The Netherlands.
49. Osborn, H., Hickok, R., Variability of Rainfall Affecting Runoff From a Semiarid Rangeland Watershed, Southwest Watershed Research Center, Tucson, Arizona, Water Resources Research, Vol. 4, No. 1, February, 1968.
50. Osborn, H., Lane, L., Precipitation--Runoff for Very Small Semiarid Rangeland Watersheds, Water Resources Research, Vol. 5, No. 2, April, 1969.
51. Pedersen, J., et al, Hydrographs by Single Linear Reservoir Model, Journal of the Hydraulics Division, Vol. 106, No. HY5, May, 1980.
52. Pilgrim, D., Travel Times and Nonlinearity of Flood Runoff From Tracer Measurements on a Small Watershed, Water Resources Research, Vol. 12, No. 3, June, 1976.
53. Pilgrim, D., Bridging the Gap Between Flood Research and Design Practice, Water Resources Research, Vol. 22, No. 9, pp. 165S-176S, August, 1986.
54. Pitman, W., Flow Generation by Catchment Models of Differing Complexity-- A Comparison of Performance, Journal of Hydrology, 38 (1978) 59-70, Elsevier Scientific Publishing Company, Amsterdam-Printed in The Netherlands.
55. Porter, J., A Comparison of Hydrologic and Hydraulic Catchment Routing Procedures Journal of Hydrology, 24, pp. 333-349, 1975.
56. Reed, D., et al, A Non-Linear Rainfall-Runoff Model, Providing for Variable Lag Time, Journal of Hydrology, 25 (1975), 295-305, North-Holland Publishing Company, Amsterdam-Printed in The Netherlands.
57. Rose, F., Hwang, G., A Study of Differences Between Streamflow Frequency and Rainfall Frequency for Small Rural Watersheds, 1985 International Symposium on Urban Hydrology, Hydraulic Infrastructures and Water Quality Control, University of Kentucky, July 23-25, 1985.
58. Ruh-Ming, Li, et al, Nonlinear Kinematic Wave Approximation for Water Routing, Water Resources Research, Vol. 11, No. 2, April, 1975.
59. Schilling, W., Fuchs, L., Errors in Stormwater Modeling--A Quantitative Assessment, Journal of Hydraulic Engineering, Vol. 112, No. 2, February, 1986.
60. Scully, D., Bender, D., Separation of Rainfall Excess from Total Rainfall, Water Resources Research, Vol. 5, No. 4, August, 1969.

61. Sorooshian, S., Gupta, V., Automatic Calibration of Conceptual Rainfall-Runoff Models: The Question of Parameter Observability and Uniqueness, Water Resources Research, Vol. 19, No. 1, February, 1983.
62. Stedinger, J., Confidence Intervals for Design Events, Journal of Hydraulic Engineering, Vol. 109, No. 1, January, 1983.
63. Stedinger, J., Design Events with Specified Flood Risk, Water Resources Research, Vol. 19, 2, pp 511-522, April, 1983.
64. Tingsanchili, T., Manandhar, S., Analytical Diffusion Model for Flood Routing, Journal of Hydraulic Engineering, Vol. 111, No. 3, March, 1985.
65. Troutman, B., An Analysis of Input in Perception-Runoff Models Using Regression With Errors in the Independent Variables, Water Resources Research, Vol. 18, No. 4, pp 947-964, August, 1982.
66. United States Department of the Interior Geological Survey, A Digital Model for Streamflow Routing by Convolution Methods, U.S. Geological Survey Water-Resources Investigations Report 83-4160.
67. U.S. Army Corps of Engineers, The Hydrologic Engineering Center, Adoption of Flood Flow Frequency Estimates at Ungaged Locations, Training Document No. 11, February, 1980.
68. U.S. Army Corps of Engineers, The Hydrologic Engineering Center, Comparative Analysis of Flood Routing Methods, Research Document No. 24, September, 1980.
69. U.S. Army Corps of Engineers, The Hydrologic Engineering Center, Continuous Hydrologic Simulation of the West Branch DuPage River Above West Chicago: An Application of Hydrocomp's HSP, Research Note No. 6.
70. U.S. Army Corps of Engineers, the Hydrologic Engineering Center, Hydrologic Analysis of Ungaged Watersheds Using HEC-1, Training Document No. 15, April, 1982.
71. U.S. Department of Transportation, Federal Highway Administration, Hydrology, Hydraulic Engineering Circular No. 19, October, 1984.
72. U.S. Army Corps of Engineers, The Hydrologic Engineering Center, Introduction and Application of Kinematic Wave Routing Techniques Using HEC-1, Training Document No. 10, May, 1979.
73. U.S. Army Corps of Engineering, The Hydrologic Engineers Center, Testing of Several Runoff Models on an Urban Watershed, Technical Paper No. 59.
74. U.S. Department of Agriculture, Soil Conservation Service, National Engineering Handbook Section 4 (NEH-4) 210-VI Amendment S. Transmission Losses, Washington, D.C., March 1, 1983.
75. Wallis, J., Wood, E., Relative Accuracy of Log Pearson III Procedures, Journal of Hydraulic Engineering, Vol. 111, No. 7, July, 1985.
76. Watt, W., Kidd, C., Quurm-A Realistic Urban Runoff Model, Journal of Hydrology, 27 (1975) 225-235, Elsevier Scientific Publishing Company, Amsterdam-Printed in The Netherlands.

77. Weinmann, E., Laurenson, E., Approximate Flood Routing Methods: A Review, Journal of The Hydraulics Division, Vol. 105, No. HY12, December, 1979.
78. Whitley, R., Hromadka II, T. V., Computing Confidence Intervals for Floods I, Microsoftware for Engineers, 1986.
79. Whitley, R., Hromadka II, T. V., Computing Confidence Intervals for Floods, II, Microsoftware for Engineers, 1986.
80. Williams, D. W., et al, TRRL and Unit Hydrograph Simulations Compared with Measurements in an Urban Catchment, Journal of Hydrology, 48 (1980), 63-70, Elsevier Scientific Publishing Company, Amsterdam-Printed in The Netherlands.
81. Zaghoul, N., SWMM Model and Level of Discretization, Journal of the Hydraulics Division, Proceedings of the American Society of Civil Engineers, ASCE, No. 107, No. HY11, November, 1981.